

INSULRAP NO TORCH 125



Maximum Underground Insulation Protection

INSULRAP "NO TORCH" 125™ is a 125 MIL SELF-ADHESIVE vapor barrier and waterproofing membrane for installation over insulation on hot or cold underground piping systems. **INSULRAP "NO TORCH" 125™** is a multi-layered "peel and stick" product providing maximum protection of buried insulated pipe systems with the labor saving ease of a peel and stick application. **INSULRAP "NO TORCH" 125™** will expand and contract to accommodate normal pipe movement and is resistant to chemicals, acids, and alkalis. **INSULRAP "NO TORCH" 125™** will tolerate higher insulation surface temperatures than our other burial membranes. The design and engineering of insulation on buried steam lines is critical to the success of the system; special care must be taken in the design of these systems, consult the insulation manufacturer for more information.

TECHNICAL DATA: INSULRAP "NO TORCH" 125™		
Total Thickness	125 mils (3.175 mm)	ASTM D 1000
Backing Thickness	6 mils (0.15 mm)	ASTM D 1000
Membrane Thickness	5 mils (0.127 mm)	ASTM D 1000
Overlap Adhesion	> 20#/in width	ASTM D 1000
Ultimate Elongation (%)	> 400%	ASTM D 882 Method A
Permeance	< .014 Perms	ASTM E 96-93 UBC
Tensile Strength Film	> 6000 PSI	ASTM D 882 Method A
Peel Adhesion	> 15#/in width	ASTM D 1000
Puncture Resistance	> 40#	ASTM E 154
Low Temperature Flexibility	No Cracks @ -15° F (-25° C)	ASTM D 146 Modified

APPLICATION INSTRUCTIONS AND PRECAUTIONS:

Materials should be stored out of the weather, moved and stored away from possible physical damage. The recommended storage temperature is 50°F to 80°F. In cool temperatures, (below 50° F) Polyguard **Cold Weather Activator** should be used to improve adhesion to the substrate. See submittal data sheet for Polyguard Cold Weather Activator products for more information on their use and application.

Prior to application, insure that the insulation is clean of all frost, moisture, fabrication dust and other any other foreign matter. Large diameter pipes require the application of **Insulrap Outerwrap** to prevent soil stress.

Though commonly factory pre-applied by qualified insulation fabricators, **INSULRAP "NO TORCH" 125™** can be applied by in the field using a 'cigarette wrap' method. The silicone coated release sheet is to be removed immediately prior to the time of application. 'Cigarette wrap' applications must provide for a 4" overlap of the membrane onto itself on both the longitudinal seam and the circumferential seam. Use pressure from a roller to insure that the lap is well conformed to the insulation surface. When 'single layered' insulation is installed on hot applications, double layering of the butt strips is recommended. If a Cold Weather Activator is used, it is applied directly to the insulation, being cautious that our solvent-based activator can erode some foam insulations. If you are installing **INSULRAP "NO TORCH" 125™** over cellular glass insulation, there is no chance of the solvent-based activator attacking the insulation. It is a known fact that our solvent-based activator will attack blue Styrofoam® insulation.



Polyguard
www.polyguardproducts.com





When applied in cool temperature conditions such as below 50°F, the adhesive surface may lose a portion of its adhesiveness. Care should be taken to make sure that **INSULRAP "NO TORCH" 125™** is fully adhered at all overlaps. The following measures will improve adhesion in cool installation conditions:

- Keep rolls of **INSULRAP "NO TORCH" 125™** in a warm storage area prior to use.
- Warm the surface of the adhesive and/or the surface being coated with a heat gun prior to application.
- **Polyguard's Low Temperature Activator** should be applied to the substrate and lap areas.
- Large diameter pipes require Insulrap Outerwrap to prevent soil stress.

WARNING: If necessary, only apply heat after the solvent based activator has thoroughly dried and no solvent vapors are present!

INSULRAP "NO TORCH" 125™ should not be left exposed to ultraviolet light for more than seven days. If for any reason it has to remain exposed, cover with a black plastic film, cardboard or any suitable material until the membrane is jacketed.

<u>Temperature Ranges:</u>	<u>Minimum</u>	<u>Maximum</u>
Application	0°F. (-17°C)	125°F. (52°C)
Insulation Surface	-25°F. (-14°C)	150°F. (82°C)

Please contact Polyguard Products for direct burial detail drawings. Consult the engineers application instructions for recommendations for wall pene-trations (*existing and new construction*), insulation supports, line guide, line anchor, expansion-contraction joints, expansion chamber and ditch con-figura-tions including drainage pipe.

INSULRAP "NO TORCH" 125™ is a vapor barrier or waterproofing membrane only. **DO NOT use our product as a substitute for banding or mechanical fastening of the pipe insulation.** Consult insulation manufacturer's instructions for fastening instructions. Insulation surface temperature should not exceed 180° F. during operation.

This material is offered for sale by **POLYGUARD PRODUCTS, INC.**, only for the expressed purpose as described in this literature for purposes other than taught therein by **POLYGUARD PRODUCTS, INC.** shall be the responsibility of the purchaser and **POLYGUARD PRODUCTS, INC.** does not warrant nor will be responsible for any misuse of these products. **POLYGUARD PRODUCTS, INC.** will replace, material not meeting our manufacturer's specifications, one year from date of sale.

POLYGUARD products as described herein are for industrial use only. The application of these products should be performed by workmen who are skilled in the application of materials described herein in accordance with manufacturer's specifications.

All Material Safety Data Sheets and precautionary labels should be read and understood by all user supervisory personnel and employees before using. Consult **POLYGUARD PRODUCTS, INC.**, Material Safety Data Sheets and OSHA regulations for additional safety and health information for the products described herein. Purchaser is responsible for complying with all applicable federal, state, or local laws and regulations covering use of the product including waste disposal. This is not a Material Safety Data Sheet and is not to be used as such. **POLYGUARD** has a Material Safety Data Sheet available.

REV 4-12-07